



- Performance characteristics:
- Main body part material
 - Insulator: PA6+30%GF (F1)/PBT+30%GF BLACK UL94 V-0
 - Contact terminal: Copper alloy, 1.27 μm min Ni under plated, outer plating see spec list
 - Electrical requirements:
 - Current rating: 3 A
 - Voltage rating: 220 V
 - Contact resistance: ≤15 mΩ
 - Insulation resistance: ≥5000 MΩ
 - Withstanding voltage: 1000 Vr.m.s, 1mA, 60s
 - Environment specification
 - Working temperature: -40°C~+105°C
 - Applicable standard: IEC60807
 - Packing & storing
 - Method of packing: Tray, inner box, outer box
 - Storing condition: temperature of -10°C~+40°C below 80% relative humidity
 - Style of installation: Panel mounting.
 - To prevent the pollution of the environment product info
 - RoHS agreement: In line with the european union RoHS

Unless otherwise specified tolerance:

| | | | |
|-----|-------|-----|-----|
| .X | ±0.50 | .X° | ±3° |
| .X | ±0.38 | .X° | ±2° |
| .XX | ±0.25 | | |

| | | | | |
|------|-----------------------|----------|-----------|------------|
| ① | 1 | 410412 | xudongbin | 2019.09.06 |
| Mark | NO. | File NO. | Signature | Date |
| DRAW | XUDONGBIN 2019.07.11 | | | |
| CHK | Lawrence 2019.09.10 | | | |
| MAN | | | | |
| STD | Juanli lai 2019.09.11 | | | |
| APP | Alan 2019.09.11 | | | |

| | | | | | | | |
|---|------|--------|-------|---------------|--|--|--|
| 1450 QDB15 Male | | | | SLO. 1450.006 | | | |
| Projection | Rev. | Weight | Scale | | | | |
| ⊕ | A1 | | | | | | |
| All Dimensions in mm | | | | Sheet 1 of 1 | | | |
| SHINNING SHENZHEN SHINNING ELECTRONIC CO., LTD. | | | | | | | |