

- Performance characteristics:
- Main body part material
Insulator: PBT BLACK UL94 V-0
Contact terminal: Copper alloy, 1.27 μm min Ni under plated, outer plating see spec list
 - Electrical requirements:
Current rating: 3 A
Voltage rating: 300 V
Contact resistance: ≤15 mΩ
Insulation resistance: ≥5000 MΩ
Withstanding voltage: 1000 Vr.m.s, 1mA, 60s
 - Environment specification
Working temperature: -40°C ~ +85°C
 - Applicable standard: IEC60807
 - Packing & storing
Method of packing: Tray, inner box, outer box
Storing condition: temperature of -10°C ~ +40°C below 80% relative humidity
 - Style of installation: Panel mounting.
 - To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS

Unless otherwise specified tolerance:

X.	±0.50	X.°	±3°
.X	±0.38	.X°	±2°
.XX	±0.25		


①	1	410412	xudongbin	2019.08.26
Mark	NO.	File NO.	Signature	Date
DRAW	XUDONGBIN 2018.10.31			
CHK	Lawrence 2019.09.10			
MAN				
STD	Juanli lai 2019.09.11			
APP	Alan 2019.09.11			

1450 QDB15 Male

1450-150-1X-1(14060743)

SL0. 1450. 004

Projection Rev. Weight Scale



A1

All Dimensions in mm Sheet 1 of 1

