



Performance characteristics:

- Main body part material
Insulator: LCP black UL94V-0
Contact terminal: Brass 1.27 μm Ni under plated,
outer plating see part number rule
- Electrical requirements:
Current rating: 3 A
Voltage rating: 250 V
Contact resistance: ≤20 mΩ
Insulation resistance: ≥5000 MΩ
Withstanding voltage: 1000 Vr.m.s, 1mA, 60s
- Mechanical requirements
Retention force: ≥10N/pin
- Environment specification
Working temperature: -55°C~+125°C
Humidity: ≤93% at 40°C
Resistance to soldering heat: 260°C±5°C, 10s
- Packing & storing
Method of packing: tray, outer box
Storing condition: temperature of -10°C~+40°C
below 80% relative humidity
- Style of installation: solder pcb installation
- To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS.

1260 - XX X - 1 X - 3

Series Code	Terminal Number 5,10,15,20,25Pin per row	Tail Length			Tail Type		Plating Code			Insulator Material&Color	
		Code	Definition		Code	Definition	Code	Definition		Code	Definition
		1	11.70	1.50	6.00	1	Straight	1	Contact Area	3	LCP Black UL94V-0
		2	13.20	3.00	6.00	8		2	Gold flash		
								8	Au 0.76 μm		Sn 3~5 μm

Unless otherwise specified tolerance:

X.	±0.50	X.°	±3°
.X	±0.38	.X°	±2°
.XX	±0.25		

①	1	230097	Jeremy	2017.07.25
Mark	NO.	File NO.	Signature	Date
DRAW			Tim Lv	2014.07.18
CHK			Tim	2017.7.27
MAN				
STD			Spring	2017.7.28
APP			Alan	2017.7.28

2.54mm Straight box Header			
1260-XXX-1X-3			

SL0. 1260. 001			
Projection	Rev.	Weight	Scale
	A1		
All Dimensions in mm		Sheet 1 of 1	
SHINNING SHENZHEN SHINNING ELECTRONIC CO.LTD.			