



P. C. B LAYOUT
TOP VIEW
Tolerance: ±0.05

Unless otherwise specified tolerance:

X.	±0.50	X.°	±3°
.X	±0.38	.X°	±2°
.XX	±0.25		

③ Performance characteristics:

1. Main body part material

Contact terminal: Metal alloy (SUS301-EH, T=0.12±0.01),
2~7.6 μm Ni under plated,
contact plating Au 0.38 μm Min.,
solder plating Au 0.08~0.6 μm Min..

2. Electrical requirements:

Current rating: 1 A
Voltage rating: 12 V DC
Contact resistance: ≤50 mΩ

3. Environment specification

Working temperature: -55°C~+125°C

4. Packing & storing

Method of packing: Reel
Storing condition: temperature of -10°C~+40°C
below 80% relative humidity

5. Style of installation: SMT

6. To prevent the pollution of the environment product info
RoHS agreement: In line with the European Union RoHS.

③	2	398965	An.Cheng	2019.07.05
Mark	NO.	File NO.	Signature	Date
DRAW	An.Cheng 2019.05.22			
CHK	Tim 2019.07.23			
MAN				
STD	Laijuanli 2019.07.25			
APP	Alan 2019.07.25			

SMT Spring

SL0.1916.039

Projection Rev. Weight Scale

B1

All Dimensions in mm Sheet 1 of 1



19163055