



P.C.B LAYOUT
Tolerance: ±0.05

- Performance characteristics:
- ① Main body part material
Insulator: PA66, Black UL94V-0
 - ② Electrical requirements:
Current rating: 4.5 Pin 4A, Other Pin 0.5A.
Voltage rating: 250 V
Insulation resistance: ≥1000 MΩ
Withstanding voltage: 500 Vr.m.s, 1mA, 60s
 - ③ Environment specification
Working temperature: -40°C~+105°C
 - ④ Packing & storing
Method of packing: Plastic bag, inner box, outer box
Storing condition: Temperature of -10°C~+40°C
below 80% relative humidity
 - ⑤ Style of installation: Applicable for crimp cable installation
 - ⑥ To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS.

Unless otherwise specified tolerance:

-	-	X.°	±3°
.X	±0.25	.X°	±2°
.XX	±0.15		

①	5	435600	An. Cheng	2020.02.25
②	1	403150	An. Cheng	2019.07.29
③	1	318475	An. Cheng	2018.07.06
Mark	NO.	File NO.	Signature	Date
DRAW			An. Cheng	2018.06.22
CHK			Tim	2020.06.05
MAN				
STD			Juanli lai	2020.06.08
APP			Alan	2020.06.08

2.54mm Pitch wafer female housing

13471001

SL0.1347.003			
Projection	Rev.	Weight	Scale
	A3		
Sheet 1		1 of 1	
SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.			