



Size table:

P/N	Pin number	A	B
3	13441023	11.78	7.92
6	13441024	23.66	19.80

Performance characteristics:

- Main body part material
Insulator: PA66 nature UL94V-0
- Electrical requirements:
Current rating: 7 A
Voltage rating: 250 V
Insulation resistance: $\geq 1000 \text{ M}\Omega$
Withstanding voltage: 1500 Vr.m.s, 1mA, 60s
- Environment specification
Working temperature: $-40^\circ\text{C} \sim +105^\circ\text{C}$
- Packing & storing
Method of packing: Plastic bag, inner box, outer box
Storing condition: Temperature of $-10^\circ\text{C} \sim +40^\circ\text{C}$
below 80% relative humidity
- Style of installation: Applicable for crimp cable installation
- To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS.

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^\circ$
.X	± 0.38	.X°	$\pm 2^\circ$
.XX	± 0.25		

Mark	NO.	File NO.	Signature	Date	3.96mm Pitch wafer female housing		SL0.1344.115			
DRAW							Projection	Rev.	Weight	Scale
CHK			An.Cheng	2011.10.28				A0		
MAN							All Dimensions in mm Sheet 1 of 1			
STD					13441023 13441024		SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.			
APP										