



Performance characteristics:

1. Main body part material
Insulator: PA66, Nature UL94V-0
2. Electrical requirements:
Current rating: 10 A
Voltage rating: 250 V
Insulation resistance: $\geq 500 \text{ M}\Omega$
Withstanding voltage: 1500 Vr.m.s, 1mA, 60s
3. Environment specification
Working temperature: $-55^{\circ}\text{C} \sim +105^{\circ}\text{C}$
4. Packing & storing
Method of packing: plastic bag, outer box
Storing condition: temperature of $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
below 80% relative humidity
5. Style of installation: applicable for crimp
cable installation
6. To prevent the pollution of the environment product info
RoHS agreement: In line with the European Union RoHS.

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^{\circ}$
.X	± 0.38	.X°	$\pm 2^{\circ}$
.XX	± 0.25		

②	2	400667	JamesZhang	2019.07.16
Mark	NO.	File NO.	Signature	Date
DRAW	Huanjiang Xu 2018.11.05			
CHK	Tim 2019.11.30			
MAN				
STD	Juanli lai 2019.12.02			
APP	Alan 2019.12.02			

5.08mm Pitch Wafer
Female Housing 2 Pin

13451007

SL0.1345.010

Projection	Rev.	Weight	Scale
	A1		
All Dimensions in mm		Sheet 1 of 1	
SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.			