



DETAIL C
SCALE 2:1

Unless otherwise specified tolerance:

X.	± 0.50	X.°	± 3°
.X	± 0.38	.X°	± 2°
.XX	± 0.25		

- Performance characteristics:
1. Main body part material
Contact terminal: Phosphor bronze(C5210-H), 1.27μm Ni under plated, outer plating Sn 3~5μm .
 2. Electrical requirements:
Current rating: 3 A
Contact resistance: ≤ 20 mΩ
Withstanding voltage: 1000 Vr.m.s, 1mA, 60s
 3. Mechanical requirements
Wire gauge: AWG 20 ~ 24
 4. Environment specification
Working temperature: -25°C ~ 80°C
Humidity: ≤ 93% at 40°C
 5. Style of installation: Applicable for crimp cable installation.
 6. To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS.



				2.54mm Pitch Receptacle Terminal		SL0.1347.103			
Mark	NO.	File NO.	Signature			Date	Projection	Rev.	Weight
DRAW		An.Cheng		2013.09.24		A0			
CHK						All Dimensions in mm			
MAN					Sheet 1 of 1				
STD					SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.				
APP					13473001				