



Performance characteristics:

1. Main body part material
Insulator: PA66, Nature UL94V-0
2. Electrical requirements:
Current rating: 10 A
Voltage rating: 250 V
Insulation resistance: $\geq 1000 \text{ M}\Omega$
Withstanding voltage: 1500 Vr.m.s, 1mA, 60s
3. Environment specification
Working temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
4. Packing & storing
Method of packing: plastic bag, outer box
Storing condition: temperature of $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
below 80% relative humidity
5. Style of installation: applicable for crimp cable installation
6. To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS.

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^{\circ}$
.X	± 0.38	.X°	$\pm 2^{\circ}$
.XX	± 0.25		

				5.08mm Pitch Wafer Female Housing 4 Pin		SL0.1345.006			
Mark	NO.	File NO.	Signature	Date	Projection		Rev.	Weight	Scale
DRAW		Deyu Kong	2017.06.14				A0		
CHK	Tim2017.6.19				All Dimensions in mm		Sheet 1 of 1		
MAN					13451003		SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.		
STD	Spring2017.6.19								
APP	ZhiJian Jiang2017.6.19								