



Performance characteristics:
 1. Main body part material
 Insulator: PA9T, Black UL94V-0
 Contact terminal: Copper Alloy, Ni 1.27µm Min. under plated,
 Contact plating Au 0.76µm Min..
 Spring: SUS
 2. Electrical requirements:
 Current rating: 1A/Pin(Signal Pin)
 Voltage rating: 250 V
 Insulation resistance: ≥1000 MΩ
 Withstanding voltage: 1000 Vr.m.s, 1mA, 60s
 3. Environment specification
 Working temperature: -40°C ~ +105°C
 4. Packing & storing
 Method of packing: Tray, inner box, outer box
 Storing condition: Temperature of -10°C ~ +40°C
 below 80% relative humidity
 5. Style of installation: Applicable for crimp cable installation
 6. To prevent the pollution of the environment product info
 RoHS agreement: In line with the European Union RoHS.

Unless otherwise specified tolerance:

-	-	X.°	±3°
.X	±0.25	.X°	±2°
.XX	±0.15		

①	1	587289	An. Cheng	2022.09.23
②	2	559794	An. Cheng	2021.05.05
③	5	499089	An. Cheng	2021.02.02
Mark	NO.	File NO.	Signature	Date
DRAW			An. Cheng	2020.10.13
CHK			Tim	2022.10. &
MAN				
STD			xyliu	2022. %& &
APP			Alan	2022. %& 2-

2.54mm Pitch wafer				SL0.1347.006			
Projection		Rev.	Weight	Scale			
		A3					
Sheet 1			1 of 1				
13476001				SHENZHEN SHINNING ELECTRONIC CO.,LTD.			