



- Performance characteristics:
1. Main body part material
Insulator: PA66 white UL94V-0
 2. Electrical requirements:
Current rating: 7 A
Voltage rating: 250 V
Insulation resistance: $\geq 1000 \text{ M}\Omega$
Withstanding voltage: 1500 Vr.m.s, 1mA, 60s
 3. Environment specification
④ Working temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
 4. Packing & storing
Method of packing: Plastic bag, inner box, outer box
Storing condition: Temperature of $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
below 80% relative humidity
 5. Style of installation: Applicable for crimp
cable installation
 6. To prevent the pollution of the environment product info
RoHS agreement; Content

Size table:

P/N	Pin number	A	B
13441012	2	8.15	3.96
13441013	3	12.11	7.92
13441014	4	16.07	11.88
13441015	5	20.03	15.84
13441016	6	23.99	19.80
13441017	7	27.95	23.76
13441018	8	31.91	27.72
13441019	9	36.00	31.68
13441020	10	39.96	35.64
13441021	11	43.92	39.60
13441022	12	47.88	43.56

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^{\circ}$
.X	± 0.38	.X°	$\pm 2^{\circ}$
.XX	± 0.25		

				3.96mm Pitch wafer female housing		SL0.1344.101				
④	1	SN-0000556	Stab	2010.6.21			Projection	Rev.	Weight	Scale
Mark	NO.	File NO.	Signature	Date				A1		
DRAW	J.A 2009-03-03									
CHK										
MAN										
STD					13441012~13441022					
APP										
							Sheet 1		1 of 1	
							SHINNING SHENZHEN SHINNING ELECTRONIC CO., LTD.			