



- Performance characteristics:
1. Main body part material
Insulator: PA66 Nature UL94V-0
 2. Electrical requirements:
Insulation resistance: $\geq 500 \text{ M}\Omega$
Withstanding voltage: 500 Vr.m.s, 1mA, 60s
 3. Mechanical requirements
Wire gauge: AWG26~30
 4. Environment specification
Working temperature: $-40^\circ\text{C} \sim +110^\circ\text{C}$
 5. Packing & storing
Method of packing: Plastic bag, outer box
Storing condition: Temperature of $-10^\circ\text{C} \sim +40^\circ\text{C}$
below 80% relative humidity
 6. Style of installation: Applicable for crimp cable installation
 7. To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS.

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^\circ$
.X	± 0.38	.X°	$\pm 2^\circ$
.XX	± 0.25		

①	1	157383	LinZhao	2016.10.18
Mark	NO.	File NO.	Signature	Date
DRAW	LinZhao 2016-09-26			
CHK	Tim2016.10.20			
MAN				
STD	Eva2016.10.23			
APP	Alan2016.10.23			

1.25mm Pitch Dual-Row wafer
female housing 2*6 Pin

13411304

SL0. 1341. 015

Projection Rev. Weight Scale

B1

All Dimensions in mm Sheet 1 of 1

SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.