



- Performance characteristics:
1. Main body part material
Insulator: PA66 Black UL94V-0
 2. Electrical requirements:
Voltage rating: 125 V
Insulation resistance: $\geq 1000 \text{ M}\Omega$ (after installation)
Withstanding voltage: 1000 Vr.m.s, 1mA, 60s (after installation)
 3. Environment specification
Working temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
 4. Packing & storing
Method of packing: Plastic bag, outer box
Storing condition: Temperature of $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
below 80% relative humidity
 5. Style of installation: Applicable for crimp cable installation
 7. To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS.

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^{\circ}$
.X	± 0.38	.X°	$\pm 2^{\circ}$
.XX	± 0.25		

①	1	411972	Tim Lv	2019.09.12
②	1	230328	Tim Lv	2017.08.23
Mark	NO.	File NO.	Signature	Date
DRAW			Tim Lv	2016.10.20
CHK			Lawrence	2019.11.21
MAN				
STD			Juanli lai	2019.11.29
APP			AJan	2019.11.29

2.00mm pitch double row housing

12301119

SLO. 1230. 008			
Projection	Rev.	Weight	Scale
	A2		
All Dimensions in mm		Sheet 1 of 1	
SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.			