



- Performance characteristics:
- Main body part material
Insulator: PA66 Nature UL94V-0
 - Electrical requirements:
Current rating: 2 A(With Terminal)
Insulation resistance: $\geq 1000 \text{ M}\Omega$
Withstanding voltage: 800 Vr.m.s, 1mA, 60s
 - Environment specification
Working temperature: $-40^\circ\text{C} \sim +105^\circ\text{C}$
 - Packing & storing
Method of packing: Plastic bag, outer box
Storing condition: Temperature of $-10^\circ\text{C} \sim +40^\circ\text{C}$
below 80% relative humidity
 - Style of installation: Applicable for crimp cable installation
 - To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS.

P/N	Pin number	A	B	C	D
13461024	2X9Pin	16.00	18.70	20.90	12.20
13461039	2X12Pin	22.00	24.70	26.90	12.20

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^\circ$
.X	± 0.38	.X°	$\pm 2^\circ$
.XX	± 0.25		

Mark	NO.	File NO.	Signature	Date
④	4	591179	KiaoWei Pan	2022.11.21
DRAW	Tim Lv 2019.01.05			
CHK				
MAN				
STD				
APP				

2.00mm Pitch wafer female housing

134610XX

SLO. 1346.016			
Projection	Rev.	Weight	Scale
	A1		
All Dimensions in mm		Sheet 1 of 1	
SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.			