



PCB Layout

Performance characteristics:

- Main body part material
Insulator: See part number rule
Contact terminal: Brass, 1.27~2μm Ni under plated, outer plating see part number rule
- Electrical requirements:
Current rating: 3 A
Voltage rating: 250 V
Contact resistance: ≤10 mΩ
Insulation resistance: ≥1000 MΩ
Withstanding voltage: 1000 Vr.m.s, 1mA, 60s
- Environment specification
Working temperature: -40°C~+105°C
Humidity: ≤93% at 40°C
- Packing & storing
Method of packing: Plastic bag, small outer box
Storing condition: Temperature of -10°C~+40°C below 80% relative humidity
- Style of installation: Solder PCB installation
- To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS.

1343 - XX X - X X - X

Series code		Terminal number		Spec code		Tail length code		Plating code			Insulator material & color	
Code	Definition	Code	Definition	Code	Definition	Code	Definition	Code	Definition	Code	Definition	
		02~15		3	THT Straight male	A	1.7	B	Sn 3~5 μm	3	LCP Black UL94V-0	
						D	2.8	6	Au0.25 μm Sn 3~5 μm	N	LCP Nature UL94V-0	
						E	2.5	7	Au0.38 μm Sn 3~5 μm	X	Customized	
						1	3.3	X	Customized			
						2	4.3					
						3	4.3					
						9	6.0					
						X	Customized					

Unless otherwise specified tolerance:

X.	±0.50	X.°	±3°
.X	±0.38	.X°	±2°
.XX	±0.25		

②	2	187308	An.Cheng	2017.02.10
Mark	NO.	File NO.	Signature	Date
DRAW		An.Cheng	2015.06.11	
CHK		Tim2017.2.14		
MAN		Spring2017.2.17		
STD		Alan2017.2.17		
APP				

2.50mm Pitch wafer
straight male

1343

SLO.1343.010

Projection	Rev.	Weight	Scale
	A1		
All Dimensions in mm		Sheet 1 of 1	
SHINNING SHENZHEN SHINNING ELECTRONIC CO. LTD.			