


PCB Layout



02PIN

Performance characteristics:

- Main body part material
Insulator: See part number rule
Contact terminal: Brass, 1.27 μm Min. Ni under plated, outer plating see part number rule
- Electrical requirements:
Current rating: 3 A
Voltage rating: 250 V
Contact resistance: ≤10 mΩ
Insulation resistance: ≥1000 MΩ
Withstanding voltage: 1000 Vr.m.s, 1mA, 60s
- Environment specification
Working temperature: -40°C~+105°C
Humidity: ≤93% at 40°C
- Packing & storing
Method of packing: Tape & reel, outer box
Storing condition: Temperature of -10°C~+40°C below 80% relative humidity
- Style of installation: Solder PCB installation
- To prevent the pollution of the environment product info
RoHS agreement: In line with the European Union RoHS.

1343 - XX X - X X - X

Series code		Terminal number		Spec code		Tail length code		Plating code		Insulator material & color	
Code	Definition	Code	Definition	Code	Definition	Code	Definition	Code	Definition	Code	Definition
		02~15		4	PIP With Cap	A	1.7	B	Sn 3 μm Min.	3	LCP Black UL94V-0
						D	2.8	6	Au0.25 μm Sn 3 μm Min.	N	LCP Nature UL94V-0
						E	2.5	7	Au0.38 μm Sn 3 μm Min.	X	Customized
						1	3.3	X	Customized		
						C	3.8				
						2	2.2				
						3	4.3				
						9	6.0				
						X	Customized				

Unless otherwise specified tolerance:

X.	±0.50	X.°	±3°
.X	±0.38	.X°	±2°
.XX	±0.25		

Mark	NO.	File NO.	Signature	Date
DRAW		An.Cheng		2020.10.28
CHK		Tim		2020.11.13
MAN				
STD		Juanli lai		2020.11.13
APP		Alan		2020.11.13

2.50mm Pitch wafer
straight male

1343

SLO.1343.058

Projection	Rev.	Weight	Scale
	A0		
All Dimensions in mm		Sheet 1 of 1	
SHINNING SHENZHEN SHINNING ELECTRONIC CO. LTD.			