



1280-000-12-1

- PLASTIC MATERIAL AND COLOR
- CONTACTS PLATING
- PITCH: 2.54mm
- TYPE: SHUT UP
- SERIES CODE

PERFORMANCE CHARACTERISTICS:

1. MAIN BODY PART MATERIAL
INSULATOR: PBT BLACK UL94V-0
CONTACT TERMINAL: PHOSPHOR BRONZE, 1.27 μm Ni UNDERPLATED, GOLD FLASH
2. ELECTRICAL REQUIREMENTS
CURRENT RATING: 3 A
CONTACT RESISTANCE: ≤ 20 mΩ
INSULATION RESISTANCE: ≥ 10000 MΩ
WITHSTANDING VOLTAGE: 650 Vr.m.s, 1mA, 60s
3. MECHANICAL REQUIREMENTS
INSERTION FORCE: ≤ 3.92 N/pin (USE 0.64mm SQUARE PIN)
EXTRACTION FORCE: ≥ 0.40 N/pin (USE 0.64mm SQUARE PIN)
4. ENVIRONMENT SPECIFICATION
WORKING TEMPERATURE: -40°C ~ +105°C
5. PACKING & STORING
METHOD OF PACKING: PLASTIC BAG
STORING CONDITION: TEMPERATURE OF -10°C ~ +40°C
BELOW 80% RELATIVE HUMIDITY
6. TO PREVENT THE POLLUTION OF THE ENVIRONMENT PRODUCT INFO
ROHS AGREEMENT: CONTENT
TECHNICS: LEAD-FREE

UNLESS OTHERWISE SPECIFIED
TOLERANCE

X.	±0.50	X.*	±3°
.X	±0.38	.X*	±2°
.XX	±0.25		

MARK	NO.	FILE NO.	SIGNATURE	DATE
DRAW		Glen	2007.8.27	
CHK		David Xu	2007.8.28	
MAN		David Xu	2007.8.28	
STD		Helen Wang	2007.8.29	
APP		James He	2007.8.29	

CLOSED TOP JUMPER

1280-000-12-1

SLO. 1280. 090			
PROJECTION	REV.	WEIGHT	SCALE
	A0		
SHEET 1		OF 1	
SHINNING SHENZHEN SHINNING ELECTRONICS CO.,LTD.			