



Unless otherwise specified tolerance:

X.	±0.50	X.°	±3°
.X	±0.38	.X°	±2°
.XX	±0.25		

Performance characteristics:

- Main body part material
Contact terminal: Phosphor bronze, 1.27μm Min. Ni under plated, outer plating Sn 3μm Min..
- Electrical requirements:
Current rating: 2A/AWG#24
Voltage rating: 100 V
Contact resistance: ≤20 mΩ
- Mechanical requirements
Wire gauge: AWG#24~28
Insertion force: ≤8 N/pin(Use 0.50mm square pin)
Extraction force: ≥0.5 N/pin(Use 0.50mm square pin)
Retention force(Housing): ≥10N/pin
- Environment specification
Working temperature: -40°C~+105°C
- Packing & storing
Number of packing: 10000pcs/reel
Method of packing: Paper reel
Storing condition: temperature of -10°C~+40°C
below 80% relative humidity
- Style of installation: With the female housing assembly
- To prevent the pollution of the environment product info
RoHS agreement: In line with the European Union RoHS

①	1	532292	Jiangbo Liu	2021.09.03
②	1	439094	Jiangbo Liu	2020.02.12
③	3	412376	Jiangbo Liu	2019.09.12
Mark	NO.	File NO.	Signature	Date
DRAW			Jiangbo Liu	2019-1-7
CHK				
MAN			Lawrence	2023.04.21
STD			xylu	2023.04.26
APP			Tim	2023.04.26

2.00mm Wafer female terminal

SL0.1346.015

Projection	Rev.	Weight	Scale
	A3		

All Dimensions in mm Sheet 1 of 1

SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.

13463008