



Packing Drawing

- Performance characteristics:
1. Main body part material
Contact terminal: Copper alloy, 1.27 μ m Min. Ni under plated, outer plating bright Sn3~5 μ m
 2. Electrical requirements:
Current rating: 3 A
Voltage rating: 250 V
Contact resistance: ≤ 20 m Ω
 3. Mechanical requirements
Wire gauge: AWG22~30
 4. Environment specification
Working temperature: -40 $^{\circ}$ C~+105 $^{\circ}$ C
 5. Packing & storing
Number of packing: 10Kpcs/reel
Method of packing: Paper reel, outer box
Storing condition: Temperature of -10 $^{\circ}$ C~+40 $^{\circ}$ C below 80% relative humidity
 6. Style of installation: Applicable for crimp cable installation
 7. To prevent the pollution of the environment product info
RoHS agreement: In line with the European Union RoHS.

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^{\circ}$
.X	± 0.38	.X°	$\pm 2^{\circ}$
.XX	± 0.25		

④	1	502370	Change Yu	2021.04.29
Mark	NO.	File NO.	Signature	Date
DRAW	Change Yu 2019.08.26			
CHK	Tim 2021.05.31			
MAN				
STD	Juanli lia 2021.06.01			
APP	Alan 2021.06.01			

2.50mm Wafer Male Terminal

13433034

SL0.1343.043

Projection	Rev.	Weight	Scale
	A1		
Sheet 1		1 of 1	
SHINNING SHENZHEN SHINNING ELECTRONIC CO., LTD.			