



N=Pin No.

Unless otherwise specified tolerance:

X.	±0.50	X.°	±3°
.X	±0.38	.X°	±2°
.XX	±0.25		

- Performance characteristics:
- Main body part material  
Insulator: PA66 Black UL94V-0
  - Electrical requirements:  
Voltage rating: 125 V  
Insulation resistance:  $\geq 1000 \text{ M}\Omega$  (after installation)  
Withstanding voltage: 1000 Vr.m.s, 1mA, 60s (after installation)
  - Environment specification  
Working temperature:  $-40^\circ\text{C} \sim +105^\circ\text{C}$
  - Packing & storing  
Method of packing: Plastic bag, outer box  
Storing condition: Temperature of  $-10^\circ\text{C} \sim +40^\circ\text{C}$   
below 80% relative humidity
  - Style of installation: Applicable for crimp cable installation
  - To prevent the pollution of the environment product info  
RoHS agreement: In line with the european union RoHS.

BOM:

P/N	Pin No.	A	B	C	D
12301204	2X04	6.00	8.20	16.00	18.00
12301206	2X06	10.00	12.20	20.00	22.00
① 12301208	2X08	14.00	16.20	24.00	26.00
12301209	2X09	16.00	18.20	26.00	28.00
12301210	2X10	18.00	20.20	28.00	30.00

①	1	591179	XiaoWei	Par	2022.11.21
②	1	520581	Change Yu		2021.06.19
③	4	268334	Change Yu		2017.12.14
Mark	NO.	File NO.	Signature	Date	
DRAW	Change Yu 2017.09.20				
CHK					
MAN					
STD					
APP					

2.00mm pitch double row housing  
123012XX

SL0. 1230. 012

Projection	Rev.	Weight	Scale
	A3		

All Dimensions in mm Sheet 1 of 1

SHINNING SHENZHEN SHINNING ELECTRONIC CO., LTD.