



Performance characteristics:

1. Main body part material
Insulator: PA66 Black UL94V-0
2. Electrical requirements:
Current rating: 4.5A for 2 pin, others 1A
Insulation resistance: $\geq 1000 \text{ M}\Omega$
Withstanding voltage: 500 Vr.m.s, 1mA, 60s
3. Environment specification
Working temperature: $-40^\circ\text{C} \sim +105^\circ\text{C}$
4. Packing & storing
Method of packing: Plastic bag, inner box, outer box
Storing condition: Temperature of $-10^\circ\text{C} \sim +40^\circ\text{C}$
below 80% relative humidity
5. Style of installation: Applicable for crimp cable installation
6. To prevent the pollution of the environment product info
RoHS agreement: In line with the european union RoHS.

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^\circ$
.X	± 0.38	.X°	$\pm 2^\circ$
.XX	± 0.25		

Mark	NO.	File NO.	Signature	Date
①	1	591199	ZhaoLin	2022.11.21
DRAW	Zhaolin 2018.12.22			
CHK				
MAN				
STD				
APP				

2.54mm pitch wafer female housing 2x3pin (HUAWEI)

SL0.1236.012

Projection	Rev.	Weight	Scale
	B1		

Sheet 1 1 of 1

12361106

SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.