



Performance characteristics:

1. Main body part material
Insulator: PA66 Nature UL94V-0
2. Electrical requirements:
Voltage rating: 250 V
Insulation resistance: $\geq 500 \text{ M}\Omega$
Withstanding voltage: 500 Vr.m.s, 1mA, 60s
3. Mechanical requirements
Mating force: 80N Max. (2*15Pin)
Unmating force: 7N Min. (2*15Pin)
Terminal Retention force: 9.8N/Pin Min.
Durability times: 10 times
4. Environment specification
Working temperature: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$
5. Packing & storing
Method of packing: Plastic bag, inner box, outer box
Storing condition: Temperature of $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
below 80% relative humidity
6. Style of installation: Applicable for crimp cable installation
7. To prevent the pollution of the environment product info
RoHS agreement: In line with the European Union RoHS.

Unless otherwise specified tolerance:

X.	± 0.50	X.°	$\pm 3^{\circ}$
.X	± 0.38	.X°	$\pm 2^{\circ}$
.XX	± 0.25		

Mark	NO.	File NO.	Signature	Date
DRAW			An.Cheng	2021.01.28
CHK			Tim	2021.01.29
MAN				
STD		Juanli lai		2021.01.30
APP		Alan		2021.01.30

2.0mm W/B DUAL RCPT HSG
(2*15Pin)

13461530

SLO. 1346. 021

Projection	Rev.	Weight	Scale
	A0		

All Dimensions in mm Sheet 1 of 1

